

STAMPCRETE LIQUID RELEASE

TECHNICAL DATA

DESCRIPTION

BASIC USE:

STAMPCRETE LIQUID RELEASE is designed to keep fresh concrete from sticking to set concrete. STAMPCRETE LIQUID RELEASE is ideal for use as a bond breaking material for rubber stamping tools.

COMPOSITION and MATERIALS:

STAMPCRETE LIQUID RELEASE is a light viscosity, easy to spray solution of polymerized organic and inorganic solids in a non-photochemically reactive solvent. The solution is free of silicones and mercuric or lead compounds.

STAMPCRETE LIQUID RELEASE contains a green marker dye to ensure full coverage of the area being treated.

This dye is a fugitive type color and dissipates within 72 hours.

PACKAGING:

STAMPCRETE LIQUID RELEASE is packed in 5-gallon (U.S.) or 18.9 Liter pails.

TECHNICAL DATA:

BOND BREAKING:

STAMPCRETE LIQUID RELEASE will leave no surface residue on concrete when properly used, resulting in clean, natural surfaces that will accept most solvent based paints and adhesives.

TECHNICAL

CHARACTERISTICS:

Solids by weight – 10%
Weight – 6.6 pounds per gallon

Surface appearance after coating application – unchanged.

Color – Green fugitive dye, dissipates within 72 hours.

INSTALLATION

APPLICATION – BOND BREAKER COAT:

STAMPCRETE LIQUID RELEASE should be applied to surface prior to placing stamping tools.

MAINTENANCE

No maintenance is required.

WARRANTY

Stampcrete International, Ltd. warrants that this product will be free from defects and will perform as represented in writing provided application of product is in accordance with manufacturer's recommendations and application instructions. Stampcrete International, Ltd will refund the purchase price of any product proven defective, but shall in no way be liable for indirect, consequential, special or resultant damaged, whether due to breach of warranty or negligence. Stampcrete International Ltd. makes no guarantee or warranty express or implied, including without

limitation, warranties of fitness or merchantability, with respect to this product.

MANUFACTURER

Stampcrete International
325 Commerce Blvd
Liverpool, NY 13088
Ph. 315-451-2837
800-233-3298
FAX 315-451-2290

E-mail:

Info@stampcrete.com

World Wide Web:

<http://www.stampcrete.com>